



Ninebot-E Specifications

Appearance	Anodized silver + porcelain, white + sky blue; light grey
Primary Materials	Magnesium alloy+ aluminum alloy+ LEXAN resin
Weight	52 lbs
Machine Size	15.4" x 23.2" x 43.3"~55.1"
Shipping Carton Sizes	Mainframe: 24.4" x 17.3" x 18.5" (50 lbs) Operation Bar: 44.9" x 5.5" x 3.7" (5 lbs)
Recommended Max Payload	230 lbs
Max. Speed	12.4 Mph
Max Range	12.4 Miles (165 lb person on flat terrain with full battery charge)
Max. Slope	20 degrees (incline / decline)
Speed Settings	Limited Speed Mode: Can be adjusted from 2.5 - 6.2 Mph (4~10Kph) Normal Speed Mode: (default mode): 6.8 - 12.4 Mph (11-20Kph)
Battery	Lithium 55V/450W
Motor	2 x 1350W
Tire/Rim Size	85/50-12 custom tires, 12" x 2.7" resin-steel fusion rims
Back-up System	Redundant electronic control system
Remote Control Keys	Multi-Function Wireless Key FOB (2 pieces)
Charger / Charge Time	1 x standard charger, 120W, 4 hours for full charge
Wireless	Bluetooth wireless connection. Remote control using 'NineDroid' Smartphone APP
NineDroid APP Display Panel	Displays battery capacity; mileage; speed; temperature; firmware versions; speed-limited mode; remote control mode; locked mode; Bluetooth connection; Warnings; and System Alerts
Handlebar Dashboard	Readable in sunlight; automatic luminance adjustment; power, mileage, speed, riding time, internal temperature, firmware, switch off limit speed mode, remote control mode, lock mode, Bluetooth connection display; alarm, fault status & code display

Remarks: Specifications above for reference only, specifications are subjected to change without prior *notification*.

Visit www.NinebotUS.com for more information

Or call NineBot U.S. at (862) 240-8494 Mon-Fri 9AM-6PM Eastern